



# Technical Note

47

---

## AN IMPROVED HYDROGEN ATOM BEAM FURNACE



---

U. S. DEPARTMENT OF COMMERCE  
NATIONAL BUREAU OF STANDARDS

# THE NATIONAL BUREAU OF STANDARDS

## Functions and Activities

The functions of the National Bureau of Standards are set forth in the Act of Congress, March 3, 1901, as amended by Congress in Public Law 619, 1950. These include the development and maintenance of the national standards of measurement and the provision of means and methods for making measurements consistent with these standards; the determination of physical constants and properties of materials; the development of methods and instruments for testing materials, devices, and structures; advisory services to government agencies on scientific and technical problems; invention and development of devices to serve special needs of the Government; and the development of standard practices, codes, and specifications. The work includes basic and applied research, development, engineering, instrumentation, testing, evaluation, calibration services, and various consultation and information services. Research projects are also performed for other government agencies when the work relates to and supplements the basic program of the Bureau or when the Bureau's unique competence is required. The scope of activities is suggested by the listing of divisions and sections on the inside of the back cover.

## Publications

The results of the Bureau's work take the form of either actual equipment and devices or published papers. These papers appear either in the Bureau's own series of publications or in the journals of professional and scientific societies. The Bureau itself publishes three periodicals available from the Government Printing Office: The Journal of Research, published in four separate sections, presents complete scientific and technical papers; the Technical News Bulletin presents summary and preliminary reports on work in progress; and Basic Radio Propagation Predictions provides data for determining the best frequencies to use for radio communications throughout the world. There are also five series of nonperiodical publications: Monographs, Applied Mathematics Series, Handbooks, Miscellaneous Publications, and Technical Notes.

Information on the Bureau's publications can be found in NBS Circular 460, Publications of the National Bureau of Standards (\$1.25) and its Supplement (\$1.50), available from the Superintendent of Documents, Government Printing Office, Washington 25, D.C.

# NATIONAL BUREAU OF STANDARDS

## Technical Note

47

MAY 1960

### AN IMPROVED HYDROGEN ATOM BEAM FURNACE

Ralph Klein and John Pararas

This research was performed under the National Bureau of Standards Free Radicals Research Program, supported by the Department of the Army.

NBS Technical Notes are designed to supplement the Bureau's regular publications program. They provide a means for making available scientific data that are of transient or limited interest. Technical Notes may be listed or referred to in the open literature. They are for sale by the Office of Technical Services, U. S. Department of Commerce, Washington 25, D. C.

DISTRIBUTED BY

UNITED STATES DEPARTMENT OF COMMERCE  
OFFICE OF TECHNICAL SERVICES  
WASHINGTON 25, D. C.

Price 50 cents



# AN IMPROVED HYDROGEN ATOM BEAM FURNACE

Ralph Klein and John Pararas

An improvement in the construction of the tungsten furnace for use in a hydrogen atom-beam apparatus has been effected by fabricating the furnace from a tungsten rod. This avoids the possibility of leakage of molecular hydrogen which may occur when the tungsten tube is made from rolled tungsten sheet, the technique used heretofore. The fabrication of the seamless furnace and the method of mounting are described.

## INTRODUCTION

In many applications of atom beam techniques involving hydrogen, it is desirable to minimize the molecule-atom ratio of the beam. Several experimental considerations affect this ratio such as the design of the vacuum system and the construction of the furnace in which the hydrogen is dissociated. It is the latter problem which will be considered in some detail.

Experiments in which surface reactions of hydrogen atoms could be observed with a field emission microscope technique required an apparatus in which a field emission microscope tube, operating at liquid helium temperature, was attached to a hydrogen atom beam source. Considerable simplification in the interpretation of the field emission patterns would result if the percentage of hydrogen molecules in the impinging beam were maintained at as low a level as possible. Further, since the emitting point presents a target of the order of  $10^{-8}$  sq. cm, a serious problem of the beam location can be avoided only if the beam cross section is sufficiently large. The intensity need not be high since even a fraction of a monolayer deposited on the emitting tip is easily observable. Considerations of this nature dictate the dimensions of the furnace, and in particular the size of the hole through which the atom effusion occurs.

Lamb and Rutherford<sup>1</sup> describe, in their notable paper on the fine structure of hydrogen, a hydrogen dissociator made by rolling .004" tungsten sheet in the form of a cylinder. A slot cut near the center provided the hydrogen outlet. It is pointed out, in the authors' description of this furnace, that there is leakage of molecular hydrogen around the ends of the cylinder. Fite<sup>2</sup> employed a similar technique, using however,

---

1 Lamb, W. E. and Rutherford, R. C., Phys. Rev. 79, 549 (1950).

2 Fite, Wade L., "Ionization of the Hydrogen Atom on Electron Impact", General Atomics Report GA267, Dec. 20, 1957.

0.001" thick tungsten foil rolled into 3/16" diameter tubes with six layers of foil making up the tube walls.

It is advantageous to construct the tungsten furnace from a solid tube with an axial hole and an appropriate central exit slot. That these have not been employed previously is to be ascribed to difficulties in fabrication. These difficulties have now been resolved, and the preparation of tungsten tube furnaces can be accomplished.<sup>1</sup> Fig. 1 is the design adopted for the application described. The furnace is made as follows: The starting blank is a tungsten rod, in this case .247" diameter. A blind hole, coaxial with the rod, is drilled with a hole .187" diameter, .062" deep being provided at the open end. The tube is then ground to give a .005" wall, as shown in the figure. Finally, the effusion hole is bored through the wall.

The success of drilling the long, narrow hole in the center of the tungsten rod depends to a great extent on the skill and experience of the fabricator. A tungsten carbide drill (carballoy 883) is used. It is shaped as shown in Fig. 2. The rod is mounted in a lathe and spun at 700 to 900 rpm, the drill being held in the tail stock. As the drilling proceeds, frequent removal of chips with a compressed air blast is required. It is important that the drill be resharpened frequently. The hole is made first with a roughing drill and completed with a finishing drill. About 8 hours are required to complete the operation.

The wall of the tube is ground to a thickness of .005" with an aluminum wheel and a sulfur base lubricant. The tube is held with a mandril of high-speed steel specially ground to accurately fit the hole in the tungsten rod. The mandril is taper locked for the grinding process. The effusion hole is drilled through the wall as the final operation on the tungsten tube. During this process, the high-speed steel mandril is replaced with a similar one of cold rolled stock. The hole may be of any size depending on the requirements of the experiment. A fine slot may be drilled if a rectangular effusion orifice is desired.

The furnace was mounted as shown in figures 3 and 4. Platinum brazing of the tungsten to the molybdenum tube proved quite satisfactory. The molybdenum tube, surrounded by two concentric cylinders for water cooling, provides for passage of molecular hydrogen (introduced through a palladium thimble) to the dissociator. The blind end of the tungsten tube is clamped by a setscrew in a molybdenum holder. The holder in turn is setscrewed to the double copper coil as shown. Water circulating through these coils provides for cooling. The molybdenum holder moves freely in a stainless steel block, thus providing for the thermal expansion of the tungsten tube.

The tungsten tube furnace is heated with alternating current from a high current transformer, the primary of which is energized by a constant voltage supply. The leads are attached to the cooling tubes, one end of

---

<sup>1</sup> The technique was devised by Mr. William Stadler of N.B.S.

the furnace being electrically isolated from the assembly head by the "alsimag" gasket, as shown in figure 2. A current of about 175 amperes with a 1-1/2 volt drop provides a steady state furnace temperature of approximately 2300°C. The temperature has been maintained at this level for eight hours of continuous operation on several occasions, and the performance of the equipment has satisfactorily fulfilled design expectations.




Fig. 1. Tungsten tube furnace for dissociating hydrogen.





Fig. 2. Tungsten carbide tool for drilling the longitudinal hole in the tungsten tube furnace.

Scale: 1 inch




Fig. 3. Mounting of tungsten tube with hydrogen inlet system.

SCALE:  
1 INCH




Fig. 4. Complete mounting of the hydrogen atomic beam source.





## NATIONAL BUREAU OF STANDARDS

A. V. Astin, Director

## THE NATIONAL BUREAU OF STANDARDS

The scope of activities of the National Bureau of Standards at its major laboratories in Washington, D.C., and Boulder, Colorado, is suggested in the following listing of the divisions and sections engaged in technical work. In general, each section carries out specialized research, development, and engineering in the field indicated by its title. A brief description of the activities, and of the resultant publications, appears on the inside of the front cover.

## WASHINGTON, D.C.

**Electricity and Electronics.** Resistance and Reactance. Electron Devices. Electrical Instruments. Magnetic Measurements. Dielectrics. Engineering Electronics. Electronic Instrumentation. Electrochemistry.

**Optics and Metrology.** Photometry and Colorimetry. Photographic Technology. Length. Engineering Metrology.

**Heat.** Temperature Physics. Thermodynamics. Cryogenic Physics. Rheology. Molecular Kinetics. Free Radicals Research.

**Atomic and Radiation Physics.** Spectroscopy. Radiometry. Mass Spectrometry. Solid State Physics. Electron Physics. Atomic Physics. Neutron Physics. Radiation Theory. Radioactivity. X-rays. High Energy Radiation. Nucleonic Instrumentation. Radiological Equipment.

**Chemistry.** Organic Coatings. Surface Chemistry. Organic Chemistry. Analytical Chemistry. Inorganic Chemistry. Electrodeposition. Molecular Structure and Properties of Gases. Physical Chemistry. Thermochemistry. Spectrochemistry. Pure Substances.

**Mechanics.** Sound. Mechanical Instruments. Fluid Mechanics. Engineering Mechanics. Mass and Scale. Capacity, Density, and Fluid Meters. Combustion Controls.

**Organic and Fibrous Materials.** Rubber. Textiles. Paper. Leather. Testing and Specifications. Polymer Structure. Plastics. Dental Research.

**Metallurgy.** Thermal Metallurgy. Chemical Metallurgy. Mechanical Metallurgy. Corrosion. Metal Physics.

**Mineral Products.** Engineering Ceramics. Glass. Refractories. Enameled Metals. Constitution and Microstructure.

**Building Technology.** Structural Engineering. Fire Protection. Air Conditioning, Heating, and Refrigeration. Floor, Roof, and Wall Coverings. Codes and Safety Standards. Heat Transfer. Concreting Materials.

**Applied Mathematics.** Numerical Analysis. Computation. Statistical Engineering. Mathematical Physics.

**Data Processing Systems.** SEAC Engineering Group. Components and Techniques. Digital Circuitry. Digital Systems. Analog Systems. Application Engineering.

• Office of Basic Instrumentation.

• Office of Weights and Measures.

## BOULDER, COLORADO

**Cryogenic Engineering.** Cryogenic Equipment. Cryogenic Processes. Properties of Materials. Gas Liquefaction.

**Radio Propagation Physics.** Upper Atmosphere Research. Ionospheric Research. Regular Propagation Services. Sun-Earth Relationships. VHF Research. Radio Warning Services. Airglow and Aurora. Radio Astronomy and Arctic Propagation.

**Radio Propagation Engineering.** Data Reduction Instrumentation. Modulation Research. Radio Noise. Tropospheric Measurements. Tropospheric Analysis. Propagation Obstacles Engineering. Radio-Meteorology. Lower Atmosphere Physics.

**Radio Standards.** High Frequency Electrical Standards. Radio Broadcast Service. High Frequency Impedance Standards. Electronic Calibration Center. Microwave Physics. Microwave Circuit Standards.

**Radio Communication and Systems.** Low Frequency and Very Low Frequency Research. High Frequency and Very High Frequency Research. Ultra High Frequency and Super High Frequency Research. Modulation Research. Antenna Research. Navigation Systems. Systems Analysis. Field Operations.

